

What is claimed is:

1. A method for upgrading a dial indicator to provide both local visible and remote indication of a physical parameter, said method comprising:
 - providing the dial indicator with a magnetic rotary pointer, said magnet rotary pointer being rotatable in response to a change in the physical parameter;
 - magnetically coupling a potentiometer to said magnet, said potentiometer being magnetically adjustable, wherein a rotation of said magnet causes a change in the electrical output of said potentiometer; and
 - fastening said potentiometer to a front side of the dial indicator.
2. The method of claim 1, wherein said providing is accomplished by securing a magnet to a rotary pointer of the dial indicator.
3. The method of claim 1, wherein said providing is accomplished by replacing a rotary pointer of the dial indicator with a replacement rotary pointer, said replacement pointer having a magnet disposed integrally therewith.
4. The method of claim 1 wherein the dial indicator comprises a liquid level indicator for a storage tank.
5. The method of claim 1 wherein the dial indicator is mounted to a liquid storage tank.
6. The method of claim 5 wherein said storage tank comprises a natural gas storage tank.
7. The method of claim 5 wherein said storage tank comprises a liquid propane storage tank.
8. The method of claim 5 wherein said storage tank comprises a liquid ammonia storage tank.

- 10

20. The method of claim 1 wherein said potentiometer is fastened to a transparent cover.
21. The method of claim 1 wherein said fastening said potentiometer comprises interposing said potentiometer between a bracket and a transparent face plate, and fastening said bracket to the dial indicator.
22. The method of claim 21 wherein said bracket comprises an optically transparent material.
23. The method of claim 22 wherein said optically transparent material comprises plastic.
24. The method of claim 1, wherein said physically coupling further comprises: removing a cover from the front face of the dial indicator; and refastening said cover to the front face of the dial indicator.
25. A kit for upgrading a dial indicator to provide both local visible and remote indication of a physical parameter, said kit comprising:
a magnet, sized and shaped for coupling to the dial indicator in a manner wherein said magnet rotates in response to a change in the measured physical parameter;
a magnetically adjustable potentiometer; and
a mounting assembly including a bracket sized and shaped for fastening said potentiometer to the dial indicator.
26. The kit of claim 25, wherein said magnet is sized and shaped for being secured to a rotary pointer of the dial indicator.
27. The kit of claim 25, wherein said magnet comprises a replacement rotary pointer.
28. The kit of claim 25 wherein said magnet comprises a horseshoe magnet.

29. The kit of claim 25 wherein said magnet comprises a bar magnet.
30. The kit of claim 25 wherein said potentiometer comprises a single-turn voltage divider.
31. The kit of claim 25 wherein said potentiometer comprises an other dial indicator, said other dial indicator including a magnetically actuatable voltage divider, said other dial indicator having a diameter less than about half that of said dial indicator.
32. The kit of claim 25 wherein said bracket comprises an optically transparent material.
33. The kit of claim 32 further comprising a remote display.
34. A dial indicator for providing both local visible and remote display of liquid level in a liquid storage tank, said dial indicator comprising:
a magnetic rotary pointer, said magnet rotary pointer being rotatable in response to a change in the liquid level in the tank;
a magnetically adjustable potentiometer including a voltage divider and at least two electrical connectors, said potentiometer being magnetically coupled to said magnetic rotary pointer wherein a rotation of said magnetic rotary pointer causes a change in the electrical output of said potentiometer;
said potentiometer being mounted to a front side of said dial indicator by a transparent bracket.
35. The dial indicator of claim 34, wherein said magnetic rotary pointer comprises a rotary pointer of the dial indicator having a magnet secured thereto.
36. The dial indicator of claim 34, wherein said magnetic rotary pointer comprises a replacement rotary pointer, said replacement pointer having a magnet disposed integrally therewith.

38. The dial indicator of claim 34, wherein said potentiometer comprises an other dial indicator, and said other dial indicator has a diameter less than about half that of said dial indicator.

[illegible]